

## BALLOON JACK



### 3 Step Balloon Jack BLPBJ23L BLPBJ23S

- ✓ These pneumatic jacks lift up to 2 T
- ✓ Operated by the triggers at the end of the handle
- ✓ The air pressure to be used should be min 7 bar, max 10 bar

### 2 Step Balloon Jack BH9BJ22SLH BH9BJ22SSH

- ✓ 2T pneumatic balloon jack with 2-step operation
- ✓ Operated by the triggers at the end of the handle
- ✓ Supplied with a 80 mm height extension
- ✓ CE certified by Official Independent Technical Inspection Association

3 Step Balloon Jack								
P/N	Capacity (tons)	Handle type	Bar	Min. height (mm)	Max. height (mm)	Package Dimension (mm)	Weight (kg)	
BLPBJ23L	2	Long	7 - 10	200	490	490*250*250	19	
BLPBJ23S	2	Short	7 - 10	200	490	1000*250*250	16	
2 Step Balloon Jack								
P/N	Capacity (tons)	Handle type	Air inlet	Bar	Min. height (mm)	Max. height (mm)	Package Dimension (mm)	Weight (kg)
BLPBJ22L	2	Long	1/4"	7 - 10	115	345	1000*65*265	18
BLPBJ22S	2	Short	1/4"	7 - 10	115	345	345*265*265	15