

SCISSOR ALIGNMENT LIFT

Blue-Point[®]

SAL 4.5M

SECURE LIFTING POWER



Blue-Point 3.5T Scissor Alignment Lift 4.5M

PRODUCT FEATURES

- Utilizes less space than conventional four-post lifts
- Compact console design, enclosed to protect electrical and hydraulic pump components and controls
- Quad counterpoised lifting system with heavy-duty cylinders to maintain a constant level from floor to full lift height
- The open front and rear platforms provide easy access to wheel alignment and maximize the service area
- Dual engaging twin interlocking serriform mechanical safety racks with a pneumatic release

Part Number: EELR759ALC1 (220-240V 1Ph 50/60Hz) / EELR759ALC3 (380-415V 3Ph 50Hz)

SPECIFICATIONS

- Primary runway length 4500 mm
- Overall length: 4980 mm
- Maximum capacity: 3500 kg
- Overall width: 2160 mm
- Runway surface width: 550 mm
- Width between runways: 920 mm
- Primary scissor max lift height: 1862 mm
- Second scissor max lift height: 456 mm
- Second runway length: 1400 mm
- Runway initial height: 330 mm
- Primary scissor lifting / Lowering time: 40-60 / 40-60 sec
- Second scissor lifting / Lowering time: 10-30 / 10-30 sec
- Shipping Weight: 2000 kg
- Non - CE compliant

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570

Indonesia: (62-21) 2258-2222

Korea: (82) 32-326-7310

Malaysia: (60-3) 8957-1938

Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262

Taiwan: (886-2) 2298-9789

Thailand: (66) 2026-3255

Vietnam: (84-28) 5414-1432

www.snapon-bluepoint.com.sg

Blue-Point is committed product innovation and improvement. Therefore, specifications listed in may change without notice. Blue-Point is a trademark of Snap-on Incorporated. All rights reserved.



Blue-Point[®]