

TWO POST LIFTS

12K

CLEAR-FLOOR SYMMETRICAL TWO-POST SERVICE LIFT



12K



HIGH STRENGTH HEAVY GAUGE STEEL COLUMNS WITH PREMIUM FEATURES

The 12k two-post lift features include; symmetrical lifting, long reaching front and rear arms, adjustable insert screw lifting pads, padded over-head shut off bar and enhancing optional accessories.

VERSATILE DESIGN

- Hydraulic design with pressure relief system is ideal for garages and tyre shops provides service solution for CAR / SUV / VAN
- Heavy duty arm restraints and double rubber door guards designed for long-lasting system and prevents damages to vehicles
- Overhead installation can be adjusted at the time of installation to suit your requirements
- 71" cylinder stroke maximizes clearance below the vehicle
- Optional lift pad height extensions can be configured to meet most vehicle's recommended pick-up points
- Superior symmetric two-post lifting

SINGLE POINT LOCK RELEASE

- Single point lock release allows the technician to disengage both of the columns simultaneously

LIFTING POWER

- Single piece overhead adds structural strength and ease of installation
- Oversized steel pulley reduces internal stress on equalization cables and provides increased durability
- Three stage front arms provide superior extended and retracted reach, providing versatile vehicle positioning for symmetric/asymmetric lifting
- Lifting arms maximize your reach to service a wide range of vehicles

STRENGTH AND SAFETY

- High grade steel and reinforced arm reduce flex
- Padded overhead safety shut off bar for improved vehicle clearance

Model: EELR738AKS

SPECIFICATIONS

Capacity: 12,000 lb (5,443 kg)
 Capacity per Arm: 1,360 kg
 Overall Height: 4,216- 4,445 mm
 Overall Width: 3,550 mm
 Maximum Lifting Height: 1,975 mm
 Width Between Columns: 2,921 mm
 Minimum Arm Reach: 910 mm
 Maximum Arm Reach: 1,386 mm
 Drive Thru width: 2,616 mm
 Floor To Overhead Shut Off: 4,051 - 4,280 mm
 Height to Lowered Lift Pad: 133 mm
 Height to Raised Low Lift Pad: 171 mm
 Lifting Speed 50 Hz Motor: 71 seconds
 Lifting Speed 60 Hz Motor: 60 seconds
 Ceiling Height Required: 4,240 to 4,470 mm
 Hydraulic Oil: ISO 32 / 46 10WT
 Power Supply: 380 VAC 3ph 50 Hz
 220 VAC 1ph 50/60 Hz

OPTIONAL ACCESSORIES

Organizer Pack for Stack Adapter Extension
 Two 6" Stack Adapter Extensions
 24" Red Column Height Extension Kit

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570
 Indonesia: (62-21) 2258-2222
 Korea: (82) 32-326-7310
 Malaysia: (60-3) 8957-1938
 Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262
 Taiwan: (886-2) 2298-9789
 Thailand: (66) 2026-3255
 Vietnam: (84-28) 5414-1432

www.hofmann-equipment.com

Hofmann is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2021 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.
 08/21

