

TWO POST LIFTS

4T

CLEAR-FLOOR SYMMETRICAL TWO-POST SERVICE LIFT



4T



ADJUSTABLE COLUMN HEIGHTS TO PROVIDE A MAXIMUM DRIVE-THROUGH CLEARANCE

The 9K Clear-Floor two-post lift provides 4,000 kg of symmetric lifting capability with adjustable height to accommodate higher profile vehicles and give extra workspace under the vehicle.

VERSATILE DESIGN

- Hydraulic design with pressure relief system is ideal for garages and tyre shops provides service solution for CAR / SUV / VAN
- Heavy duty arm restraints and double rubber door guards designed for long-lasting system and prevents damages to vehicles

SINGLE POINT LOCK RELEASE

- Single point, air actuated lock release allows the technician to disengage both of the columns simultaneously

LIFTING POWER

- Symmetrical lifting arms configuration ideal for long wheelbase vehicles
- Three stage front arms provide superior extended and retracted reach, providing versatile vehicle positioning for symmetric/ asymmetric lifting
- Lifting arms maximize your reach to service a wide range of vehicles

STRENGTH AND SAFETY

- High grade steel and reinforced arm reduce flex
- Single piece overhead adds structural strength and ease of installation
- Rubber door guards secure against door to column damage
- Dual function overhead shut-off, quick-release plug and emergency stop with key lock that ensure user's safety

Model: EELR736A

SPECIFICATIONS

Capacity: 4,000 kg
 Capacity per arm: 1,000 kg
 Overall Height: 3,880 or 3,871 mm
 Overall Width: 3,621 or 3,871 mm
 Maximum Lifting Height: 1,900 mm
 Width Between Columns: 2,997 or 2,747 mm
 Arm Retracted Length: 720 mm
 Arm Extended Length: 1,320 mm
 Drive Thru width: 2,415 or 2,665 mm
 Height to Lowered Lift Pad: 104 mm
 Height to Raised Lift Pad: 169 mm
 Lifting Time: 40 - 60 seconds
 Lowering Time: 25 - 70 seconds
 Hydraulic Oil: ISO 32 / 46 10WT
 Max. Operating Pressure: 3,000 psi
 Power Supply: 380 VAC 3ph 50 Hz
 220 VAC 1ph 50/60 Hz

OPTIONAL ACCESSORIES

Organizer Pack for Stack Adapter Extension
 3" and 6" Height Extensions Adaptors

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570
 Indonesia: (62-21) 2258-2222
 Korea: (82) 32-326-7310
 Malaysia: (60-3) 8957-1938
 Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262
 Taiwan: (886-2) 2298-9789
 Thailand: (66) 2026-3255
 Vietnam: (84-28) 5414-1432

www.hofmann-equipment.com

Hofmann is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2021 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.
 08/21

