

TYRE CHANGER

monty®

TYRE CHANGERS

3300-22

22" SMARTSPEED CAR TYRE CHANGER



HOFMANN® 

MONTY® 3300-22 SMARTSPEED



TYRE CHANGER

MAXIMUM ERGONOMIC CLEARANCE FOR MAXIMUM PRODUCTIVITY

The tyre changer for use in general service shops and tyre shops with medium tyre service volume - with pneumatic tilt-back post, 22" outside clamping capability and smartSpeed technology.

SMARTSPEED

- The new exclusive self-adjustable speed system with inverter technology
- Automatic speed control by inverter that maximises speed depending on the torque applied
- First speed as low as 7 rpm for critical tasks
- Second speed automatically adjusted to between 7 and 18 rpm depending on the torque applied

SMARTSPEED™

- Optimises the torque applied to the wheel and automatically sets the maximum rotation speed of the wheel accordingly

ROBUST DESIGN

- Textured surface finishing to withstand the demanding environment of a workshop
- Strong and rugged design of all components ensures long life
- Special design of the tilt-back post guarantees minimum tension even when hard tyres are mounted or demounted
- Two clamping cylinders and pneumatically locked post provides a powerful and uniform clamping pressure
- Self-centering four-jaw turntable controlled by two clamping cylinders and pneumatically locked post

SAFETY

- Equipped with a double-acting bead breaking cylinder and an oversize bead breaker blade which protect tyre and rim
- Center-clamp design with covered sliding grooves ensure operator safety
- Pressure limiter, air filter and oil reservoir for lubricant to ensure the safe operation and durability of the machine
- Pedal is positioned away from the bead breaker with a guard, preventing the operator from accidentally stepping on and activating it while standing next to the bead breaker

Model: EEWH761A

SPECIFICATIONS

Inner clamping range: 12" - 24"
Outer clamping range: 10" - 22"
Max. rim width: 13"
Max. wheel diameter: 1000 mm
Bead breaking force: 12 kN
Compression air supply: 7 - 12 bar
Chuck speed: 7 - 18 rpm
Weight: 441 lb (200 kg)
Power Requirements: 230 VAC 1ph 50/60 Hz
415 VAC 3ph 50/60 Hz

STANDARD ACCESSORIES

Tyre mounting lever
Pressure gauge bar
Plastic rim protection
Roller – Tool

OPTIONAL ACCESSORIES

Plastic Mount/Demount Head with Quick Exchange Tool Kit
+6" adaptor
Light truck adaptor
Quick exchange device
Motorcycle mounting head, adaptor and bead breaker blade
MH320 pro mounting help

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570
Indonesia: (62-21) 2258-2222
Korea: (82) 32-326-7310
Malaysia: (60-3) 8957-1938
Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262
Taiwan: (886-2) 2298-9789
Thailand: (66) 2026-3255
Vietnam: (84-28) 5414-1432

www.hofmann-equipment.com

Hofmann is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2021 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.
08/21

