

ALIGNMENT LIFT

3.5T

SCISSOR-ON-SCISSOR ALIGNMENT LIFT





QUALITY WORKMANSHIP, INTUITIVE AND EASE OF OPERATION

Sleek, low-profile design works really well in shops with small spaces. It provides a flawless platform for quick service or fast repair work.

SPACE SAVING DESIGN

- Utilizes less space than conventional four-post lifts
- Lifts straight up with no for or aft movement
- Compact console design, enclosed to protect electrical and hydraulic pump components and controls

EASY WORK ACCESS

- Open front design provides easy access to alignment service and calibration areas of vehicles
- Starts lower - 13" (330 mm) drive-on height
- Lifts high: 73" (1,860 mm) full height for easy work access
- Optional long approach ramps allow gentle drive on for low profile vehicles

STRENGTH AND SAFETY

- Adjustable turnplate pocket depth ensures level positioning of turnplates
- Composite high-strength steel construction
- Powder coat finishing with non-skid runway platform surface

Model: EELR734AC (4 meter)
EELR734AP (4.5 meter)

SPECIFICATIONS

Capacity: 3,500 kg

Overall Length: 4 meters: 4,480 mm
4.5 meters: 4,980 mm

Overall Width: 2,160 mm

Width Between Platforms : 920 mm

Drive-on Height: 330 mm

Primary Scissor

Platform Length: 4 meters: 4,000 mm
4.5 meters: 4,500 mm

Platform Width: 620 mm

Platform Raised Height: 1,862 mm

Lifting / Lowering Time: 40 - 60 seconds

Rear Slip Plate Length: 1,500 mm

Front Turntable Length: 475 mm

Secondary Scissor

Platform Length: 1,400 mm

Platforms Width: 620 mm

Platform Raised Height: 456 mm

Lifting / Lowering Time: 10 - 30 Seconds

Max. Operating Pressure: 3045 psi

Hydraulic Oil: ISO 32

Air Supply Required: 7 – 8 bar

Power supply: 380 VAC 3ph 50 Hz
220 VAC 1ph 50/60 Hz

Shipping Weight: 4,409 lb (2,000 kg)

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570

Indonesia: (62-21) 2258-2222

Korea: (82) 32-326-7310

Malaysia: (60-3) 8957-1938

Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262

Taiwan: (886-2) 2298-9789

Thailand: (66) 2026-3255

Vietnam: (84-28) 5414-1432

www.hofmann-equipment.com

Hofmann is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2021 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

09/22