

TWO POST LIFT



PROFESSIONAL AUTOMOTIVE LIFT SOLUTION PREMIUM FEATURES

Automotive / general purpose lifts are packed with premium features

INTRODUCING THE **4T** BASEPLATE SYMMETRICAL
2 POST SERVICE LIFT

JohnBean

THE 4T BASEPLATE TWO-POST SERVICE LIFT

COMPLEMENTS A GREATER VARIETY OF VEHICLES FASTER AND EASIER



FEATURES

- Hydraulic two-post lift is ideal for garages and tire shops provides service solution for CAR / SUV / VAN
- Baseplate with low column design provides a solution for low ceiling workshop
- Symmetrical lifting arms configuration ideal for long wheelbase vehicles
- The two-stage front and rear arms maximize your reach to service a wide range of vehicles
- Extremely rugged design made of a single solid piece column profile guarantees utmost stability
- Controls positioned in an ergonomic place on primary column with clear indication of each push button
- Rubber door guards secure against door to column damage
- Single point safety lock release system

Model: EELR515A

SPECIFICATIONS

- Capacity: 4,000 kg
- Capacity per arm: 1,000 kg
- Overall Height: 2,831 mm
- Overall Width: 3,440 or 3,685 mm
- Maximum Lifting Height: 1,865 mm
- Width Between Columns: 2,752 or 2,665 mm
- Arm Retracted Length: 720 mm
- Arm Extended Length: 1,320 mm
- Drive Thru width: 2,410 or 2,665 mm
- Height to Lowered Lift Pad: 95 mm
- Height to Raised Lift Pad: 137 mm
- Lifting Time: 68 seconds
- Lowering Time: 42 seconds

- Hydraulic Oil: ISO 32 / 46 10WT
- Max. Operating Pressure: 2683 psi
- Power Supply:
380 VAC 3ph 50 Hz
220 VAC 1ph 50/60 Hz

OPTIONAL ACCESSORIES

- Organizer Pack for Stack Adapter Extension
- Two 6" Stack Adapter Extensions
- 24" Red Column Height Extension Kit

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570
Indonesia: (62-21) 2258-2222
Korea: (82) 32-326-7310
Malaysia: (60-3) 8957-1938
Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262
Taiwan: (886-2) 2298-9789
Thailand: (66) 2026-3255
Vietnam: (84-28) 5414-1432

www.johnbean.com

John Bean is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2020 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

06/21

JohnBean