

ALIGNMENT LIFT



PROFESSIONAL ALIGNMENT LIFT SOLUTION PREMIUM FEATURES

Unmatched productivity, performance and value

INTRODUCING THE **12K** SCISSOR WHEEL
ALIGNMENT LIFT

JohnBean

THE 12K SCISSOR WHEEL ALIGNMENT LIFT

EASY TO OPERATE WITH VERSATILE HEAVY-DUTY LIFTING CAPABILITIES

FEATURES

- ◊ Utilizes less space than conventional four-post lifts
- ◊ Lifts straight up with no for or aft movement
- ◊ Compact console design, enclosed to protect electrical and hydraulic pump components and controls
- ◊ Quad counterpoised lifting system with four heavy-duty cylinders to maintain a constant level from floor to full lift height with reinforcing rear-mounted cross member
- ◊ Dual engaging twin interlocking serriform mechanical safety racks with a pneumatic release
- ◊ Reinforced 24" wide Pro-Style runways accommodate a wide vehicle range
- ◊ Open front design provides easy access to alignment service and calibration areas of vehicles
- ◊ Gliding bearings are captured, providing durable and smooth lift operation
- ◊ Optional approach ramps expand to 87", easing loading of lower profile vehicles. Approach ramps can be retracted to 35" in order save space when not in use

Model: EELR525AKS (Flush mount)
EELR501AKS (Surface mount)

SPECIFICATIONS

- Capacity: 12,000 lbs (5,443 kg)
- Overall Length: 6,147 - 7,468 mm
- Overall Width: 2,286 mm
- Width Between Runways: 1,016 mm
- Four Wheel Alignment Wheelbase:
89" - 158" (2,260 - 4,010 mm)
- Two Wheel Alignment Wheelbase:
Up to 165" (4,190 mm)
- Platform Length: 4,550 mm
- Platform Width: 610 mm
- Platform Raised Height: 1,778 mm
- Lifting / Lowering Time: 45 - 95 seconds
- Hydraulic Oil: ISO 32 / 46 10WT
- Air Supply Required: 6 - 9 bar
- Power supply:
380 VAC 3ph 50 Hz,
220 VAC 1ph 50/60 Hz
- Shipping Weight: 6,615 lb (3,000 kg)

ROLLER JACK (OPTIONAL)

- Capacity: 6,000 (2,722 kg)
- Minimum Working Height with Adapter and Standard Pad
- Installed: 102 mm
- Fully Raised Without Extension Adapter:
375 mm
- Minimum / Maximum Arm Reach:
940 / 1,422 mm
- Roller Jack Extension Adapter:
2.44" (62 mm)

For more information, please contact our sales representatives at esales@snapon.com

Singapore: (65) 6451-5570
Indonesia: (62-21) 2258-2222
Korea: (82) 32-326-7310
Malaysia: (60-3) 8957-1938
Myanmar, Cambodia, Laos: (65) 6451-5570

Philippines: (63-2) 8-843-7935 / (63-2) 8-843-8262
Taiwan: (886-2) 2298-9789
Thailand: (66) 2026-3255
Vietnam: (84-28) 5414-1432

www.johnbean.com

John Bean is committed product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2020 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

06/21

JohnBean