

# 5T Clear Floor Two-Post Lift

## Heavy-duty Power with Maximum Reach

### EELRBP790AC2 / EELRBP790AC4

### FEATURES

- ✓ 5-ton lifting capacity, ideal for independent and local OEM workshops with heavy-duty application
- ✓ Padded overhead safety shut off bar for raised vehicle protection
- ✓ Symmetrical lifting arms configuration ideal for long wheelbase vehicles
- ✓ The three-stage front and two-stage rear arms maximize your reach to service a wide range of vehicles
- ✓ Extra wide 3 meters inside column width for service larger vehicles and better access
- ✓ Extremely rugged design made of a two-stage column profile guarantees utmost stability
- ✓ 98 mm minimum arm pad height for easy service to low pick-up vehicles
- ✓ Single point safety lock release system
- ✓ Reliability test to 3,000 cycles



Model: M2PL 5CF-WLP			
Part Number			
EELRBP790AC2: 200-240 VAC1, 50/60Hz		EELRBP790AC4: 380-415 VAC3, 50Hz,	
Type of Lift	Capacity	Capacity Per Arm	Overall Width
Symmetrical	5,000 kg	1,250 kg	3,620 mm
Width between Columns	Drive-Thru Width	Overall Height	Under Bar Clearance
3,000 mm	2,705 mm	4,100 mm	3,888 mm
Height to Lowered Lift Pad	Height to Raised Low Lift Pad	Front Arm Retracted Length	Rear Arm Retracted Length
98 mm	156 mm	660 mm	910 mm
Front Arm Extended Length	Rear Arm Extended Length	Maximum Lifting Height	Maximum Operating Pressure
1,050 mm	1,350 mm	1,975 mm	21 MPa
Hydraulic Oil Specification	Hydraulic Oil Capacity	Lift Time / Lower Time	
ISO 32/46 10WT	12L	40-60 / 25-70 seconds *Time may vary depending on the weight of the vehicle.	